


7 in (178mm) Bottom w/ 6.75 in (171mm) 7-8 Lobe 3.3 Stage HR SERIES 3



Bit Size Range	8-1/2 - 9-7/8 in	216 - 251 mm
Bit Box Connection	4-1/2 REGULAR	
Dynamic Bearing Load On/Off Bottom	151925 lbf	67600 daN
Static Bearing Load On/Off Bottom	509765 lbf	226800 daN
Max. Overpull (For Re-run)	509765 lbf	226800 daN
Absolute Overpull	742200 lbf	330100 daN
Adjustable Makeup Torque	32000 ft-lbs	43400 Nm
Stab/Thread Protector Makeup Torque	15000 ft-lbs	20300 Nm
A = Bit to Stabilizer (Centre)	17 in	0.43 m
B = Bit to Bend	Adjustable 68 in Fixed 56.3 in	1.73 m 1.43 m
C = Overall (With Dump Sub)	376.5 in	9.56 m
Weight	2948 lb	1337 kg

Lobe Configuration	7-8 Lobe 3.3 Stage HR	
Displacement (No Load)	0.15 rev/gal	0.04 rev/l
Max. Differential (Full Load)	560 psi	3861 kPa
Max. Torque	9400 ft-lbs	12745 Nm
Max. Power	136 HP	101 kW

Flow Rate		Speed
GPM	LPM	RPM
300	51136	31 - 50
450	1703	54 - 70
600	2271	76 - 90



Possible damage may occur when motor is run higher than 70% of Maximum Differential Pressure.

ADJUSTABLE BUILD RATE

Hole Size	SLICK				STABILIZED			
	8-1/2 (216mm)	8-3/4 (222mm)	9-7/8 (251mm)	9-7/8 (251mm)	8-1/2 (216mm)	8-3/4 (222mm)	9-7/8 (251mm)	9-7/8 (251mm)
BEND ANGLE	Degrees per 100 Feet (30m)				Degrees per 100 Feet (30m)			
0.39	0.9	0.3	-	-	2.1	2.3	2.9	2.9
0.78	3.5	2.9	0.2	0.2	4.4	4.5	5.2	5.2
1.15	6.0	5.4	2.7	2.7	6.5	6.6	7.3	7.3
1.50	8.3	7.7	5.0	5.0	8.4	8.6	9.2	9.2
1.83	10.6	9.9	7.2	7.2	10.6	10.4	11.1	11.1
2.12	12.5	11.9	9.2	9.2	12.5	12.1	12.7	12.7
2.38	14.2	13.6	10.9	10.9	14.2	13.6	14.2	14.2
2.60	15.7	15.1	12.4	12.4	15.7	15.1	15.5	15.5
2.77	16.8	16.2	13.5	13.5	16.8	16.2	16.4	16.4
2.90	17.7	17.1	14.4	14.4	17.7	17.1	17.2	17.2
2.97	18.2	17.6	14.9	14.9	18.2	17.6	17.6	17.6
3.00	18.4	17.8	15.1	15.1	18.4	17.8	17.7	17.7

Note: Stabilizers are 1/8" undergauge

FBH BUILD RATE


Hole Size	SLICK				STABILIZED			
	8-1/2 (216mm)	8-3/4 (222mm)	9-7/8 (251mm)	9-7/8 (251mm)	8-1/2 (216mm)	8-3/4 (222mm)	9-7/8 (251mm)	9-7/8 (251mm)
BEND ANGLE	Degrees per 100 Feet (30m)				Degrees per 100 Feet (30m)			
1.25	6.3	5.6	2.4	2.4	7.3	7.5	8.1	8.1
1.50	8.0	7.2	4.0	4.0	8.8	8.9	9.6	9.6
1.75	9.6	8.9	5.7	5.7	10.3	10.4	11.1	11.1
2.00	11.3	10.6	7.4	7.4	11.7	11.9	12.5	12.5
2.25	13.0	12.3	9.1	9.1	13.2	13.4	14.0	14.0
2.50	14.7	13.9	10.7	10.7	14.7	14.8	15.5	15.5

This information is for reference only. Build rates are theoretical calculations using three-point geometry and new motor builds. Actual rate predictions will depend on formation characteristics, bit profiles, and WOB.

For custom motor configurations and build rates, please contact your DYNOMAX office.

FISHING DIMENSIONS

USC - IMPERIAL (Lengths, Diameters = in)
SI - METRIC (Lengths = m, Diameters = mm)



EXTERNALS		USC	SI
END CAP	A	11.2	0.28
BEARING HOUSING	B	--	--
PISTON HOUSING	C	17.8	0.45
STABILIZER SHOULDER	D	34.3	0.87
KICK/FIXED HOUSING	E	44.9	1.14
BIT TO BEND (ADJUSTABLE)	F1	68.0	1.73
ADAPTOR HOUSING (ADJUSTABLE)	G1	73.9	1.88
BIT TO BEND (FIXED)	F2	56.3	1.43
ADAPTOR HOUSING (FIXED)	G2	66.5	1.69
STATOR START	H	98.5	2.50
STATOR END	I	343.5	8.72
OVERALL LENGTH	J	376.5	9.56
BIT BOX Ø	K	6.38	162.1
END CAP/BEARING HOUSING Ø	L	7.00	177.8
THREAD PROTECTOR Ø	M	7.75	196.9
PISTON HOUSING Ø	N	7.15	181.6
KICK/FIXED HOUSING Ø	O	7.15	181.6
PAD (ADJUSTABLE) Ø	P1	7.38	187.5
PAD (FIXED) Ø	P2	7.38	187.5
ADJUSTABLE MANDREL PIN Ø	Q	4.22	107.2
ADAPTOR HOUSING Ø	R	7.15	181.6
ADAPTOR PIN Ø	S	4.80	121.9
STATOR TUBE OUTER Ø	T	6.75	171.5
STATOR TUBE INNER Ø	U	5.50	139.7
ROTOR CATCH SUB BLADE Ø	V	7.00	177.8
ROTOR CATCH SUB Ø	W	6.81	173.0



INTERNALS		USC	SI
BIT BOX	A	10.0	0.25
THRUST SHOULDER	B	22.9	0.58
WASHPIPE START	C	28.0	0.71
HEX END	D	34.2	0.87
BEARING ASSEMBLY ADAPTOR	E	43.1	1.09
BAA CAP	F	58.8	1.49
ROTOR ADAPTOR CAP	G	90.6	2.30
ROTOR START	H	99.2	2.52
ROTOR END	I	337.7	8.58
CATCH STEM	J	355.2	9.02
BIT BOX Ø	K	6.38	162.1
MANDREL Ø	L	5.25	133.4
THRUST Ø	M	4.49	114.0
WASHPIPE LARGE Ø	N	5.50	139.7
WASHPIPE SMALL Ø	O	4.25	108.0
BEARING ASSEMBLY ADAPTOR Ø	P	5.00	127.0
DRIVESHAFT Ø	Q	3.00	76.2
ROTOR ADAPTOR Ø	R	5.00	127.0
ROTOR MAJOR DIA. Ø	S	4.50	114.3
ROTOR CATCH STEM Ø	T	3.19	81.0

This information is for reference only. Assemblies are displayed in an "Adjustable Configuration"

Rotor Catch and Rotor Catch Float Sub Lengths may vary based on configuration, and use of Dump Subs or combination Rotor Catch and Float Housings.

If any additional information is required, please contact your local DYNOMAX office.